

DS_2000

by Dr. D. B. Hanchate

FILE	DS_2000.PDF (2.57M)		
TIME SUBMITTED	29 JAN 2017 06:54PM	WORD COUNT	545
SUBMISSION ID	759814697	CHARACTER COUNT	3119

Dr. Dinesh Bhagwan Hanchate, VP's KBIET, Baramati

S		C		H		E		D		U		L		E	
		PERIOD 1		PERIOD 2		PERIOD 3		PERIOD 4		PERIOD 5		PERIOD 6		PERIOD 7	
TIME	FROM	TO	FROM	TO	FROM	TO	FROM	TO	FROM	TO	FROM	TO	FROM	TO	FROM
SUBJECT	MONDAY														
TEACHER	MONDAY														
SUBJECT	TUESDAY														
TEACHER	TUESDAY														
SUBJECT	WEDNESDAY														
TEACHER	WEDNESDAY														
SUBJECT	THURSDAY														
TEACHER	THURSDAY														
SUBJECT	FRIDAY														
TEACHER	FRIDAY														
SUBJECT	SATURDAY														
TEACHER	SATURDAY														

RECESS TIME : From am to pm

LUNCH TIME : From am to pm

This book is made from **TNPL'S** environment friendly bagasse based paper.



~~Hamchale~~

UNIT I : —

Introduction to Data Structures

*) Algorithm:- An algorithm is a finite set of instruction to accomplish a particular task. Every algorithm must satisfy the foll. criteria.

ii) Input :- There are zero or more quantities which are externally supplied.

i) output:- At least one quantity is produced.

ii) Definiteness:- Each instruction must be clear and unambiguous.

iv) Finiteness:- If we trace out the instruction, then for all cases the algorithm will terminate after finite no. of steps.

x) Effectiveness :- Every instruction must be sufficiently basic that it can be carried out by a person easily.

Ex:- a) Write algorithm to search an element from the array of 'n' elements.

```

SEARCH (A, n, x)
/* A is array of size 0 to n-1 */
/* x is the element to be
   Searched */
declare i, j : integers
i = 0
j = n
while (i < j)
{
  if (A[i] == x)
  {
    print "Found"
    return
  }
  i = i + 1
}
print "Not found"
end /* End of Search */

```

* Data :- In general data is input quantity or value and is processed by algorithm.

* Data types :- It refers to the type of quantities that variables may hold in a programming language. Every programming language has a set of inbuilt data types (int, char, etc) and instructions which

manipulates the variables of this data types, but some other data types cannot be handled/manipulated by instructions (e.g. :- structure, record) known as user defined data types.

* Data object :- Data object is a term referring to a set of elements denoted by 'D'.

ex D = { JAN, FEB, MARCH, --- }.

D = { 0, 1, 2, --- }.

Now, we want to describe the set of operations which may legally applied to

This implies that we must specify the set of operations and show how they work.

ex:- Structure natno

```

declare
  ISZERO (x) → ZERO boolean - 1
  SUCC (natno) → natno - 2
  ADD (natno, natno) → natno - 3
  ZERO ( ) → TRUE - 4
  for all x, y ∈ natno Let - 5
  ISZERO (ZERO) :: = TRUE - 6
  ADD (x, ZERO) :: = x - 7
  ADD (SUCC (x), y) :: = SUCC (ADD (x, y)) - 8

```

end for. - 9
end natno - 10.

⇒ 0 → ZERO
1 → SUCC(ZERO)
2 → SUCC(SUCC(ZERO))

* Data Structure :- A data structure is a set of domains 'D', a designated domain 'd', a set of functions 'F' and a set of axioms 'A' and d ∈ D. The triple (D, F, A) denote a data structure 'd'.

Here,
$$\begin{aligned} D &= \{ \text{boolean}, \text{natno} \} \\ d &= \text{natno} \\ F &= \{ \text{ISZERO}, \text{SUCC}, \text{ADD}, \text{ZERO} \} \\ \text{AXIOMS} &= \{ \text{Statements from 6 to 8} \} \end{aligned}$$

(in previous ex.)

ex:- Structure boolean
declare
ISTRUE (boolean) → boolean
AND (boolean, boolean) → boolean

for all $a, b \in \text{boolean}$, let

ISTRUE (TRUE) ::= TRUE

ISTRUE (FALSE) ::= FALSE

ISTRUE (a) ::= if a is TRUE then TRUE
else FALSE.

AND (a, b) ::= if ISTRUE (a) and
ISTRUE (b) ISTRUE
then TRUE, else FALSE.

* Triple (DFA) is called abstract data type → The set of axioms describe the meaning & show that how function works, but they cannot be in the form of representation so that one can implement it directly (i.e. in executable form). At this stage data structure should be designed so that we know what it does, but not necessarily how it will do it.

* How to analysis the algorithm:-

(i) Frequency count:- It is the total no. of times the statement executed.

(ii) Time complexity of algorithm:- It is the time required to execute a algorithm.

ex- Addition of 'n' numbers.

```

Add()
{
    // freq count
    read n          - 1
    for (i=1 to n)  - n+1
    {
        x = z + i    - n
    }
    Print x          - 1
}

```

Total freqⁿ count = $5 + 2n$
 $\approx n$

Time complexity = $O(n)$
OR $= O(n)$

ex- A program to calculate & print max. value &

```

→ LARG (A, n)          - 1
{
    // A(1:n) // (Array is from 1 to n)
    for max = A(1)      - 1
    for (i=2 to n)      - n
    {
        if (max < A(i))
        {
            max = A(i)
        }
    }
    print 'max = ' max  - 1
}

```

Total freqⁿ count = $3 + n + 2(n-1)$
 $\approx 2(n-1)$
 $\approx n-1$

∴ Time complexity = $O(n-1)$

ex- write a algorithm for matrix addition & calculate its time complexity.

```

→ MAT_ADD (A, B, C, m, n)
{
    // A(0:m-1, 0:n-1) //
    // B(0:m-1, 0:n-1) //
    // C(0:m-1, 0:n-1) //
    for (i=0 to m-1)  - (m+1)
    for (j=0 to n-1)  - n(n+1)
    {
        C(i,j) = A(i,j) + B(i,j)
    }
}

```

Time complexity = $m \times n$

ex- To sort n element using Bubble sort & calculate time complexity.

```

→ Bubble (A, n)
{
    // A(0:n-1)
    for (i=0 to n-1)  - n+1
    for (j=0 to n-i-1) - n(n-1)
    {
        if (A[j] > A[j+1])
        {
            exchange
        }
    }
}

```

$$\begin{aligned}
 \text{Time complexity} &= (n-1) + (n-2) + (n-3) \\
 &+ \dots + 3 + 2 + 1 \\
 &= \left[n + (n-1) + (n-2) + (n-3) + \dots + 3 + 2 + 1 \right] - n \\
 &= \frac{n(n+1)}{2} - n \\
 &= \frac{n(n-1)}{2}
 \end{aligned}$$

ex - Calculate time complexity of algorithm of sequential search.

```

→ Search (A, n, x)
{
  // A[0:n-1]
  for (i = 0 to n-1)
  {
    if (x == A[i])
    {
      print 'Found'
      return
    }
  }
  print 'not Found'
}

```

$$\therefore \text{Time complexity} = 1 + 2 + \dots + n$$

$$= \frac{n(n+1)}{2}$$

$$= \frac{n^2}{2}$$

$$= \frac{n+1}{2}$$

* Ordered Lists →

It is one of the simplest & commonly used data types. In this items are arranged by some order.
ex:- Days of week = (MON, TUE, WED, ... SUN).

operation of given list:-

- i) Reading / List
- ii) Searching
- iii) Insertion - (does not overwrite)
- iv) Addition - (overwrites)
- v) Deletion.

* Array:- The most common way to represent an ordered list is by an array.

ex:- Array A = (a₁, ..., a_n)

where a_i is item / value
& i is the index.

Array item a_i & a_{i+1} store into consecutive memory location i & i+1 respectively. This is known as sequential mapping technique. Array elements can be accessed randomly.

* Data Structure of the array:-

structure ARRAY (Value, index)

declare CREATE() → Array

RETRIVE (Array, index) → value

STORE (Array, Index, value) → Array

for all $A \in \text{Array}$, $i, j \in \text{index}$, $x \in \text{value}$

CREATE() → declare A(1:n)

RETRIVE (CREATE, i) → error

RETRIVE (A, i) → if $1 \leq i \leq n$ then A(i)
else out of size

RETRIVE (STORE (A, i, x), j) → if $i = j$ then x
else RETRIVE (A, j).

end

end ARRAY

* STACKS :-

A stack is an ordered list in which all insertion & deletion are made at one end called top.

In the stack the last element to be inserted into the stack will be the 1st to be removed. Hence stack is a last in, first out (LIFO) list.



* Data Structure of Stack :-

structure STACK (item)

declare CREATE() → Stack

INSERTION (Stack) →

ADD (Stack, item) → Stack

DELETE (Stack) → Stack

TOP (Stack) → item

ISEMITS (Stack) → boolean.

for all $S \in \text{Stack}$, $x \in \text{item}$ let

CREATE() → declare S(1:n), top ← 0

ADD (S, x) → if top >= n then
print 'STACK FULL'
else { top = top + 1
S(top) ← x
}

DELETE (CREATE) → error

ISEMITS (CREATE) → TRUE.

ISEMITS (ADD(S, x)) → FALSE.

TOP (CREATE) → error

TOP (ADD(S, x)) → if top >= n then
print 'STACK FULL'
else x

TOP (S) → if ISEMITS then print
'STACK EMPTY'
else S(top).

end

end Stack

PAGE NO. :
DATE : 18/01/2000

PAGE NO. :
DATE : / /

* Algorithm for ADD and DELETE :-
OR (PUSH) OR (POP)

```
Add (Stack, top, n, item)
{
  // stack (1:n)

```

```
  if (top == n)

```

```
  {
    print 'STACK FULL'
    return

```

```
  }
  top = top + 1
  stack[top] = item
}
```

```
Delete (Stack, n, top)
{

```

```
  if (top < 0)

```

```
  {
    print 'STACK EMPTY'
    return

```

```
  }
  top = top - 1
}
```

* Implement the foll. funcm calls :-

```
(*) main()
{
  // fun1() fun3()
  // fun1(); fun3(); x = fun4();
}
```

Note down the status of stack at the time of each funcm execution. [MENU - Call Stack]

(*) i) main ()

```
{
  int i = 0;
  printf ("%d %d %d", &i++, ++i, i);
}
```

ii) main ()

```
{
  int i = 0
  printf ("%d %d %d", &i++, i, i);
}
```

iii) main ()

```
{
  i = 0
  printf ("%d %d %d", i, ++i, &++i);
}
What will be o/p after execution of printf. Justify your answer.
```

* Data object Queue :-

A Queue is a type of ordered list in which all insertions take place at one end called rear and all the deletions take place at

other end called front. The first element which is inserted into the queue will be the first one to be removed. For this reason queue are also known as first in first out (FIFO) list.

To implement a queue 2 variables front and rear are required. Front is always less than actual front of queue and rear always points to the last element in the queue.

* Data Structure of queue:-

Structure QUEUE (item)

declare CREATE () $\rightarrow$ queue

ADD (item, queue) $\rightarrow$ queue

DELETE (queue) $\rightarrow$ queue

FRONT (queue) $\rightarrow$ item

ISEMPT/REAR (queue) $\rightarrow$ Boolean

for all $Q \in \text{queue}$, $i \in \text{item}$ let

CREATE () $::=$ declare $Q(1:n)$, front = rear = 0

ISEMPT (CREATE) $::=$ TRUE

ISEMPT (ADD (i, Q)) $::=$ FALSE

DELETE (CREATE) $::=$ error

ADD (i, Q) $::=$ if (rear = n)

```
{
  print 'QUEUE_FULL'
  return
}
```

```
else
{
```

```
  rear = rear + 1
```

```
  Q (rear) = i
}
```

```
DELETE (Q)  $::=$  if (front = rear)
```

```
{
  print 'QUEUE_EMPTY'
```

```
  return
}
```

```
else
```

```
  front = front + 1
```

```
FRONT (CREATE)  $::=$  error
```

```
FRONT (ADD (i, Q))  $::=$  if ISEMPT (Q) then i
  else FRONT (Q).
```

```
end
```

```
end QUEUE
```

* Algorithm for ADD & DELETE in queue:-

ADD (item, Q, n, rear)

```
{ // Q (1:n)
```

```
  if (rear = n)
```

```
  {
    print 'QUEUE_FULL'
```

```
  }
  return
}
```

```

rear = rear + 1
@ (rear) = item

```

```

}

```

```

DELETE (Q, r, front)

```

```

{

```

```

if (front == rear)

```

```

{

```

```

    print ' @ EMPTY'

```

```

    return

```

```

}

```

```

front = front + 1

```

```

}

```

#include <stdio.h>
#define N 20
int top = -1;

global

```

/* Stack operations */

```

```

void Delete (int stack [20], int n)

```

```

{
    int tmp;

```

```

    tmp = stack [top];

```

```

    top = top - 1;

```

```

    return tmp;

```

```

}

```

```

void

```

```

Add (int stack [20], int item, int n)

```

```

{

```

```

    if (top == n - 1)

```

```

    {
        printf ("STACK FULL");

```

```

        return;

```

```

    }

```

```

top = top + 1

```

```

stack [top] = item;

```

```

}

```

```

void Print (int stack [20])

```

```

{

```

```

    if (top <= -1)

```

```

    {
        printf ("\n STACK EMPTY");

```

```

        return;

```

```

    }

```

```

    printf ("%d", stack [top]);

```

```

}

```

```

main ()

```

```

{
    int top = -1;

```

```

    char choice; int x, stack [20];

```

```

    while (1)

```

```

    {

```

```

        printf ("Add");

```

```

        printf ("Delete");

```

```

        printf ("Print");

```

```

        printf ("Exit");

```

```

        scanf ("%c", &choice);

```

```

        switch (choice)

```

```

        {

```

```

            case 'A' :

```

```

            {

```

```

                int tmp;

```

```

                scanf ("%d", &tmp);

```

```

                Add (stack, tmp, 20);

```

```

            }

```

```

            break;

```


To declare
variable
tmp.

```

case 'D': Delete(stack, 20);
           break;
case 'P': Print(stack);
           break;
case 'E': exit(0);
}
}
}

```

* Circular queue :- The efficient way is to represent linear queue with circular queue.



* Algorithm for ADD/DELETE in circular queue :-

```

ADD(Q, front, rear, n, item)
{
    // Q(0:n-1)
    rear = (rear + 1) mod n // To restart queue, i.e. after n = recd 0 cell will be active.
    if (front == rear)
    {
        Print('Q - Full')
        rear = (rear - 1) mod n
        return
    }
    Q[rear] = item;
}

```

```

DELETE(Q, front, rear, n)
{
    // Q(0:n-1)
    if (front == rear)
    {
        print 'Q - EMPTY'
        return
    }
    front = (front + 1) mod n
}

```

* Also Algorithm for ADD-DEL, in circular queue with tag ->

DATE: / /

PAGE NO.:
DATE: / /

```


ADD (Q, front, rear, n, item, tag)
{
    // tag is boolean variable which store either 0 or 1
    if ((rear == front) and tag == 1)
    {
        print 'Q_FULL'
        return
    }
    tag = 0
    rear = (rear + 1) mod n
    Q[rear] = item
}

```

```

DELETE (Q, front, rear, n, tag)
{
    if ((rear == front) and tag == 0)
    {
        print 'Q - EMPTY'
        return
    }
    tag = 1
    front = (front + 1) mod n
}

```



* Assign 3 →

Implement a circular queue using array. Implement all operation such as Addition, Deletion and print rear most element of queue. (without stack).

* Application of stack →

Types of expression: -
 i) Infix $\text{exp}^r \rightarrow$ { Polish exp^r
 — infix, postfix,
 prefix }

ex: $\{(a+b/c) / (bxc)\}$
 unary operator

In infix exp^r all operator (excluding unary operator) comes in between operand.

ii) Postfix exp^r :- In this exp^r operators comes after operand on which it operates.

Infix Postfix
 ex: $a+b \Rightarrow ab+$
 $((a*b)+c) \Rightarrow ab*c+$

iii) Prefix exp^r :- In this exp^r the operator comes before the operand on which it operates.

ex: $a+b \Rightarrow +ab$
 $((a*b)+c) \Rightarrow +(*ab)c$

* Conversion of infix expr to postfix
expr :-

i) $(a+b) \Rightarrow ab+$

ii) $((a+b)*c) \Rightarrow ab+c*$

iii) $((a+b)/(c+d)) \Rightarrow ab+cd+/$

iv) $a+b+c$
 $= ((a+b)+c) \Rightarrow ab+ct$

* Infix to Postfix $\rightarrow$


Advantages of postfix expr:-

- No paranthesis is required.
- Priority is also not important.
- Easy evaluation of expr than infix expr.
- Expression can be evaluated by just scanning left to right (in single scan).


eg $(a+(b/(c*d)))$

$\Rightarrow abcd*/+$


i) $T_1 = c*d$



ii) $T_2 = b/T_1$



iii) $T_3 = a+T_2$



* Algorithm for conversion of infix to postfix

{ Priorities of operators $\rightarrow$

Symbol	In stack priority (ISP)	In-coming priority (ICP)
--------	-------------------------	--------------------------

(Exponential)	* * or ^ or ↑	3	4
---------------	---------------	---	---

	* , /	2	2
--	-------	---	---

	+ , -	1	1
--	-------	---	---

	{ , (	0	4
--	-------	---	---

	(, #	-1	-
--	-------	----	---

ex:- $a+b*c$

if $ISP < ICP$ push

@ $-1 < 1$, @ $1 < 2$

print $\rightarrow abc*+$



if $ISP \geq ICP$ then POP

ex:- $(a+b)*c$

@ $a+b$





@ $ab+c*$




DATE: / /

PAGE NO. 1
DATE: / /


ex:- $a * b + c$



ex:- $a + b + c$



ex:- ~~$a + b = a$~~ $a \wedge b - a * b$



Asgn - 4 →

Algorithm for conversion from infix to postfix expr.

```

Define stacksize n:20
declare global top: integer
top = -1
POSTFIX()
{
  declare stack (0:n-1): character
  top = 0
  stack(top) = '#'
  while(1)
  {
    read(x) // x: character
    {
      case: x = '(': while (stack(top) != ')')
      {
        print stack(top)
        top = top - 1
      }
      top = top + 1 // remove stack
      top 'x' symbol.
      break;
    }
    case: x = ';': while (stack(top) != '#')
    {
      print stack(top)
      top = top - 1
    }
    return;
  }
}

```

```
case: x = '*' or '/' or '+' or '-' or '^';
```

```
while (ISP(stack[top]) >= ICP(x))
```

```
{
    print stack[top]
}
```

```
ADD(stack, x) // Add x onto stack
break
```

```
default: // x is operand
    print(x)
```

```
}
```

```
// end of while
```

```
// end of postfix
```

```
* ISP(y)
```

```
// y: character
```

```
{
    x =
    case: '^': return(3)
```

```
case: x = '*' or '/': return(2)
```

```
case: x = '+' or '-': return(1)
```

```
case: x = '#': return(-1)
```

```
case: x = '(': return(0)
```

```
* ADD(stack, x)
```

```
{
    if top = n-1
```

```
{
    print STACK_FULL
```

```
exit(0);
}
```

```
top = top + 1
```

```
stack[top] = x
```


```
}
```

```
* Assign - Postfix to Infix :-
```

```
* Multiple Stacks :-
```

A single dimensional array of size (i.m) can be used to represent more than one stack. Initially array can be added into required no. of stacks (say n)

ex:- The foll. fig. shows division of single array into no. of (arrays) stacks



B - (Boundary) T → (top)

1	1	1	1	1st stack - B(1) to B(2)
3	2	6	2	2nd - B(2) to B(3)
7	3	7	3	3rd - B(3) to B(4)
11	4	11	4	4th - B(4) upto end of array
15	5			

if T(1) = B(2) - stack 1 is full.

if T(1) = B(1) - stack 1 is empty.

8 so on ...

Initial conditions:-

a) Initially:-

B	T	
-1	-1	for $0 \leq i \leq 3$
3	3	
7	7	$B(i) = T(i)$
11	11	

For each stack i , $B(i)$ is used to hold the boundary values & shows the initial values of $T(i)$.

* Algorithms for ADD & DELETE:-

ADD (i , item)

{ // n is no. of stacks,
 $0 \leq i \leq n-1$ //

if $T(i) = B(i+1)$

{
 print STACK i is FULL
 return;
}

else $T(i) = T(i) + 1$ STACK($T(i)$) = item


}

Delete (i)

{
 if $T(i) = B(i)$
 {
 print stack i is EMPTY
 return
}
 $Top(i) = T(i) - 1$
}

* Multiple Queue:→

(Short note)



ssta

EMPTY :- $B(i) = F(i) = R(i)$ FULL :- $R(i) = B(i+1)$


PAGE NO. _____
DATE: / /

PAGE NO. _____
DATE: / /

* Double ended Queue :- (DEQUE)

theory


It is a one dimensional array.
We can use both the ends of array
for the additⁿ & deletⁿ operations.



if $L = R$ — Queue empty.


if $(L = 1) \& (R = n)$ — Queue Full.

(*) initially —




DD i)


left



ii)



iii)



FULL — $R = n - 1$ (left)

$R = 0$ (right).

Empty — $F = R$

$F = R$

*

Priority queue :-

(Theory)

i) Explanaⁿ.

ii) types

iii) operatⁿ.

i)

Ascending priority queue.


ii)

Descending priority queue.



*

Assign :- A program to implement a
circular queue without tag.
(ADD - DELETE - PRINT).

Device a formula in terms of front, rear, n
(n - size of queue) & (1/n), to calculate
total no. of element in that circular
queue.



ADDITION OF ELEMENT IN LINKED LIST



Node
Data
Link
Field
Dynamic mem.
d.


LINKED LIST :-

DATE : 10/02/2020
PAGE NO. :

Drawbacks of sequential representation:-
Order list may be vary in size, causes the wastage of memory.
ex:- Array of max. size 'm'.
Order list is maintain in this array having 'n' elements such that

consecutive memory location.
ex:- array, stack, queue.
One of way to represent order list is by sequential representation. In this elements are stored into consecutive memory location.

Adv - i) No consecutive mem locam.
ii) Insertion is possible without shifting data.
iii) Size of array can be increased at Run time.




DATE : 10/02/2020
PAGE NO. :

DATE: / /

31/02/2020

(a)
no. of element $< m$, then $(m-n)$ is
The wastage.



ii) Once The array of max. size is declared one cannot add elements larger than the array size. This is because static memory allocation.

iii) Insertion & deletion operation requires large of data movement and hence more time is required.



To overcome the above drawback another representation known as 'linked lists' are used.

* Linked representation:-

In linked representation element may be placed any where in memory. To access the element in correct order with each element we store the address of the next element. With each data element a pointer is associated to point the next.

element, called link. A link and data element collectively called 'node'.

Refer fig (a), (b), (c):



* Insertion:-

Consider a ordered list (10, 20, 30, 50) is maintained using linked representation. Now, insert new element 40 in betn 30 and 50.

Algorithm:-

Step 1:- Allocate a new node, say x
Step 2:- Set the data field of x to 40.


DATE: / /

PAGE NO.:

DATE: 8/2/2017

Step 3:- Set the linked field of x to ^{addr. of} node after 30 with contain 50.

Step 4:- Set the link field of a node containing 30 to x .




* Deletion:-

Delete 40 in above list.

Step 1:- Find the node which is before 40, say y .

Step 2:- Set a link field of y to the node pointed by link field of x .


Step 3:- Free the node x (deallocate it).



* Storage Pool:-

Linked list is a chain of nodes.

To create a linked list memory is divided into nodes such that each node must have at least one link field.



Memory Block

Initially the linked list is empty and all pre nodes are kept together to form a block. Such a block is known as 'Storage Pool', in another word the storage pool contains all the node that are not currently being used.

The 2 operations performed on a storage pool:-

(i) GETNODE(x):-

It removes one free node from storage pool and return its address in

' x '.

(ii) ^{ref. or procedure} _{in text}
 P4-115

same as
(malloc
in C)

i.e. x is how a pointer to that node.
If no node is free in the pool,
it return error message & stops.

ii)
(procedure)
pg-117

RET(x):-

The IT returns node x back to
the storage pool.

Q)

Consider a node has two fields, say
data and link. Let X be a pointer to
the first node in single linked list.
Write a procedure to insert the
new node at the end of linked list.
If Initially if linked list is empty
then X be a pointer to the newly
created node.

NODE : DATA & LINK

Insert (X , data)

```
{
  // X be a pointer to 1st node
  // data is variable's value that
  // you want to insert in node.
  // link field of last node contains
```

GETNODE (y) // create new node: y

LINK (y) = ϕ

DATA (y) = data

if $X = \phi$


```
{
  X = y
  return
}
```

else

```
{
  T = X
  while (LINK(T) !=  $\phi$ )
  {
    T = LINK(T)
  }
  LINK(T) = y
  return
}
```

Q)

Let $P = (X_1, X_2, \dots, X_j, \dots, X_n)$ be a linked list
where X_i is a node having 2 fields
DATA & LINK and $1 \leq i \leq n$. Let X be
a pointer to X_j ($1 \leq j \leq n$). Write a
procedure to add new node 'Y' after
 X_j so that linked list will be,
 $(X_1, X_2, \dots, X_j, Y, X_{j+1}, \dots, X_n)$



Insert (P, X, Y)

```
{
    // P is pointer to 1st node.
    // X is ——— to xj node.
    // Y is ——— new node.

```



LINK(Y) = LINK(X)

LINK(X) = Y

}

- Q) Let P be a pointer to the 1st node in a single linked list. Write a procedure to add ^{a new} node 'y' before the node X where 'X' is an arbitrary node in the list. If, $P = \phi$ then Y should be reset to point to the new first node.

Let 'P' be a pointer to first node and X is an arbitrary node in the list. Write a procedure to add new node Y before X. If $X = P$ then P should be reset to point to new first node Y.



Case (b) Insert (P, X, Y)

{

if (P = X)

{

LINK(Y) = P

P = Y

return

}

else

Case (c) { T = P

while (LINK(T) = X) (To find add of node Pn-2).

{ T = LINK(T)

}

LINK(Y) = X


LINK(T) = Y

return

}

}

- a) Let $P = (P_1, P_2, \dots, P_n)$ be a single linked list where $P_i, 1 \leq i \leq n$ is a node having two fields DATA and LINK. X is a pointer pointing to any one of the node of the linked list. Write the algorithm to delete node x from the linked list if $X=P$ then P should be reset to point to the new ^{next node} node as a first node.



DELETE (X, P)

{
if (X = P)

{

X = LINK(P)

RET(P)

P = X

}

GETNODE (t).

t = P

OR (LINK(t) = X)

while ((t->data != X->data))


{

t->link = X->link; LINK(t) = LINK(X)

free (X)

}

- b) Inverted Linked list :-




- Ex1) Let $T = (T_1, T_2, \dots, T_n)$ be a linked list. Write algorithm to invert the linked list so that after the execution $T = (T_n, \dots, T_2, T_1)$.

- Ex2) Let P be a pointer to 1st node in single linked list and X is arbitrary node in that list. Write an algorithm to add node y before X . If $X=P$ then P should be reset to pt. to the new first node y and if $X= \text{NULL}$ then add new node y at the end of the list.

* Use of Linked list to represent polynomial :-


$3x^2 + x + 10$ — polynomial.



Polynomial addition using linked

1st :-

$$\begin{array}{r} 3x^2 + x + 10 \\ + 3x^3 + 2x^2 + x \\ \hline 3x^3 + 5x^2 + 2x + 10 \end{array}$$



1st Compare power of P and Q.

If equal add else increment Q

and again compare.

If addition take place increment P along with Q.

Struct Node

```
{
    int data;
    struct Node * link;
} * Head, * New, * Tmp;
```

void Add (void)

```
{
    int n;
```

```
printf ("Enter new value");
scanf ("%d", &n);
new = (struct Node *) malloc (sizeof (struct Node));
New -> link = '0';
New -> data = n;
Tmp = Head;
while (Tmp -> link != '0')
{
    Tmp = Tmp -> link;
}
Tmp -> link = New;
}

void Insert (void)
```

```
{
    int n, t;
```

```
printf ("Enter new value");
```

```
New = (struct Node *) malloc
```

```
New -> link = '0';
```

```
New -> data = n;
```

```
printf ("Enter the value where new value is to be inserted");
```

```
scanf ("%d", &t);
```

```
Tmp = Head;
```

```
if (Head -> data == t)
```

```
{
    New -> link = Head;
```

```
Head = New;
```

```
return;
```



```

Tmp = Head;
while (Tmp->link->data != t)
{
    Tmp = Tmp->link;
}
New->link = Tmp->link;
Tmp->link = New;
}

```

```

void Delete (void)
{

```

```

    printf ("Enter the data to be deleted");
    scanf ("%d", &t);
    if (Head->data == t)
    {
        Tmp = Head;
        Head = Head->link;
        free (Tmp);
    }
    Tmp = Head;
    while (Tmp->link->data != t)
    {
        Tmp = Tmp->link;
    }
    Tmp2 = Tmp->link;
    Tmp->link = Tmp->link->link;
    free (Tmp2);
}

```

```

main ()
{

```

```

    char choice;
    while (1)
    {
        printf ("Addition");
        printf ("Deletion");
        printf ("List");
        printf ("Exit");
        choice = getch();
        switch (choice)

```

```

        {
            case 'A': if (Head == '\0')
            {
                Head = (struct Node*) malloc;
                scanf ("%d", &Head);
                Head->link = '\0';
            }

```

```

            else
            {
                Add ();
            }
            break;

```

```

            case 'I': (A)

```

```

            else
            {
                Insert ();
            }
            break;

```

```

            case 'D': if (Head == '\0')
            {
                printf ("Empty");
            }

```

```

else
{ Delete(); }
break;
case 'P' - - -
case 'E' - - -

```

* Program for Polynomial addition :-

```

struct Poly
{
    int COEF;
    int EXP;
    struct Poly *link;
} *x, *y, *z, *tmp, *t;

main()
{
    int n, i, coef;
    x = y = z = '\0';
    printf("Enter first polynomial expr");
    scanf("%d", &n)    (no. of expr.
                       z = x + y)
    for (i = n; i >= 0; i--)
    {
        printf("\n Enter the coefficient of
        position '%d', i);
        scanf("%d", &coef);
        if (coef != 0)
        {
            tmp = (struct Poly *) malloc(sizeof
            (struct Poly))
            tmp->COEF = coef;
            tmp->EXP = i;

```

1/2 3x + 2x^2

```

tmp->link = '\0';
if (x == '\0')
{
    x = tmp;
}
else
{
    while (tmp->link != NULL)
    {
        tmp = tmp->link;
    }
    tmp->link = tmp;
}
} /* End of for */

```

```

printf("Enter 2nd polynomial expr");

```

← (scan 2nd polynomial)

```

while (x->link != '\0' && y->link != '\0')
{
    if (x->EXP < y->EXP)
    {
        tmp = (struct Poly *) malloc - -
        tmp->EXP = y->EXP;
        tmp->COEF = y->COEF;
        tmp->link = ('\0');
        if (z == '\0')

```

```

{
    z = tmp;
}
else
{
    t = z;
    while (t->link != '0')
    {
        t = t->link;
    }
    t->link = tmp;
}
y = y->link;
} /* End of if */
if (x->EXP > y->EXP)
{
    { store x in z using tmp &
      increment x }
    //
}
if (x->EXP == y->EXP)
{
    tmp = (struct Poly *) malloc
    tmp->EXP = y->EXP
    tmp->COEF = x->COEF + y->COEF
    tmp->link = '0'
    if (z == '0')
    {
        z = tmp;
    }
    else
    {
        t = z;
    }
}

```

```

while (t->link != '0')
{
    t = t->link;
}
t->link = tmp;
}
y = y->link;
x = x->link;
} /* End of if */
} /* End of while */
while (y->link != '0')
{
    tmp = (struct Poly *) malloc
    tmp->EXP = y->EXP;
    tmp->COEF = y->COEF;
    tmp->link = '0';
    if (z == '0')
    {
        z = tmp;
    }
    else
    {
        t = z;
    }
    while (t->link != '0')
    {
        t = t->link;
    }
    t->link = tmp;
    y = y->link;
} /* End of while */

```

Q) How are stacks implemented

Using linked lists?

```

while (x->link != '0')
{
    // (same as above)
}

```

```

Print → while (z != 0)
{
    printf("%d %d \n", z->COEF, z->EXP);
    z = z->link;
}
} // END OF MAIN //

```

Algorithm for Polynomial addition.

```

Create Poly (x).
Create Poly (y).
z = Empty.
if (EXP(x) < EXP(y))
{
    Create New Node at end of z
    EXP(NEW) = EXP(y)
    COEF(NEW) = COEF(y)
    y = LINK(y)
}
if (EXP(x) > EXP(y))
{
    // ...
}
}

```

```

if (EXP(x) == EXP(y))
{
    Create NEW at end of z.
    EXP(NEW) = EXP(y)
    COEF(NEW) = COEF(x) + COEF(y)
    x = LINK(x)
    y = LINK(y)
}

```

```

while (y->link != NULL)
{
    attach (y) to z
    y = link (y)
}
// Similarly for x, LINK(x) = NULL

```

LINKED STACK :-

(10, 5, 11) - top → NULL

Initially: - 1st top → [10 | φ]

2nd: - top → [5 |] → [10 | φ]

3rd: - top → [11 |] → [5 |] → [10 | φ]

Algorithm :- (To add & delete in linked stack)

Add (s, item)

```

{
    // s is a stack using single linked
    // top is a pointer to top
    // most element of stack s.
}

```



```

GETNODE (NEW)
LINK (NEW) = TOP
TOP = NEW
data (NEW) = item.

```

Refer sig for
insert node
at top

```

DELETE ()

```

```

{
  if (TOP == NULL)
  {
    print 'Stack Empty'
    return
  }

```

Let X be pt. to node top = LINK (top)
before top node RET (X)
top = X
X = LINK (top)
free (X)

(X is a temp.
pointer)

* Linked Queue :-

```

front = rear = NULL
Add Q (item)

```

```

{
  GETNODE (NEW) → LINK (NEW) = NULL
  DATA (NEW) = item
  if (rear == NULL)
  {
    front = rear = NEW
    return
  }

```

else

```

{ LINK (rear) = NEW
  rear = NEW
}

```

```

DELETE Q ()

```


```

{
  if (front == NULL)
  {
    print 'Q Empty'
    return
  }

```

X = front (X is a temp.
pointer)
front = LINK (front)
RET (X)

* Circular Singly Linked Queue :-




head node :- it contains no data.

a) Initial condition :-




b) After adding one node




DATE: / /

PAGE NO: / /
DATE: / /

* Doubly Linked list :-



Circular doubly linked list ->



=> Circular Doubly linked list ->

```
* struct NODE
{
    int data;
    struct NODE *Llink;
    struct NODE *Rlink;
} *Head, *New, *Tmp;
```

void Insert (void)

```
{
    int x, h;

    printf("\n Enter value to insert");
    scanf ("%d", &x);
    printf("\n After which value you
    have to insert");
    scanf ("%d", &h);
```

/* Search value 'n' first */

```
Tmp = Head;
// Tmp = Tmp -> Rlink;
do while (Tmp != Head)
{
    if (Tmp -> data == x)
    {
        New = (struct Node *) malloc (sizeof(-));
        New -> Llink = Tmp;
        New -> Rlink = Tmp -> Rlink;
        Tmp -> Rlink -> Llink = New;
        Tmp -> Rlink = New;
        Tmp -> data = x;
        return;
    }
    Tmp = Tmp -> Rlink;
} while (Tmp != Head);
printf ("Value not found\n");
} /* end of insert */
```

Void Delete (void)

```
{
    int x;
    printf ("which element to be delete?");
    scanf ("%d", &x);
    Tmp = Head;
    do
    {
        if (Tmp -> data == x)
```

```

{
    Tmp → LLink → RLink = Tmp → RLink;
    Tmp → RLink → LLink = Tmp → LLink;
    return;
}
Tmp = Tmp → RLink;
} while (Tmp != Head);

```

```

void Print (void)
{
    // ...
}

```

```

main ()
{

```

```

    char choice;
    while (1)
    {
        printf ("In [I]nserion");
        printf ("In [D]eletion");
        printf ("In [P]rint");
        printf ("In [E]xit");
        printf ("In Enter your choice");
        choice = getch();
    }

```

```

    if (choice == 'I')
    {
        Head = (struct NODE*) malloc (sizeof
            (struct NODE));
        Head → LLink = Head → RLink = Head;
    }

```

```

    switch (choice)
    {

```

```

        case 'I': Insert ();
        break;
        case 'D': Delete ();
        break;
        case 'P': Print (); break;
        case 'E': exit (0);
    }
}
// end of main # /

```

* Linear Linked list :- (chain)

(S.N) It is a set of ordered list and connected together with the help of a linked field. Each element is stored in the node and in linear linked list the last link field of last node contain 'NULL'.

+
e.g. T → [] → [] → [] → [] → φ

In a linear linked list only way to search a node which is before p is to start back from the beginning. To avoid the searching from first node again & again the linked field of last node points to the first and such a list is called as Circular singly linked list.


Again by making the list circular, it is very easy to manipulate the list. eg. To add the node, one can add it before any node in a circular linked list. But in linear linked list there are 2 cases, either before or after a node.

* Doubly Linked List :-

→ Doubly linked list is a collection of nodes. Each node contains three fields, i) DATA, ii) RLINK, iii) LLINK. DATA field is used to store the element. RLINK is used to point right node & LLINK is used to point left node.

eg:- 
Linear doubly linked list.

ii) Circular doubly linked list.



a) Head node :- It is the first node in a linked list.

Zero linked list has to be created as a special case in algorithm.

eg:- Addition of new node. In this case if the linked list is zero then new node will become now 1st node in linked list. To avoid this special case the head node is used.

Add (T, N)

```
{
  // T is a pointer to a node
  // after which new node will be added.
```

LINK(N) = T

RLINK(N) = RLINK(T)

LLINK(RLINK(T)) = N

RLINK(T) = N

Del (T, N)

```
{
  // T is a pointer to first node.
  // N → node to be deleted.
```

RLINK(LLINK(N)) = RLINK(N)

LLINK(RLINK(N)) = LLINK(N)

free(N)

* Strings :-

 $S = S_1 S_2 \dots S_n$

set

where S_i is the character over the characterthen S is called string.length of $S = \text{no. of characters in that}$ if $\text{length}(S) = 0 \rightarrow$ it is called as ^{string} Null string.

* Data representations for string:-

i) Array (Sequential representation)

eg:- "This is"

blank space

T	h	i	s		i	s		
---	---	---	---	--	---	---	--	--

a) String ~~for~~ sequential representation is not efficient when insertⁿ & deleteⁿ into and from resp. from middle of string are carried out.

b) Locations are reserved for string having fixed size, suppose n . If the string whose size is less than n then the remaining memory is wastage.

ii) Linked representation:-

→ a) with node size = n

Suppose ($n=4$) & [String = "Welcome"]

data	Link	Link
W	e	c
m	e	

Suppose $n=5$

to indicate end of string

W	e	c		
m	e			

b) With node size always = 1

eg:- "This is"

T	h	i	s		i	s	
---	---	---	---	--	---	---	--

Operations on string:-

→ Searching → char.
→ substring.

strmp → String matching.

str_ → Pattern matching (whether given string is substring of given string)

strcat → Concatenation.

→ Reversing.

strlen → String length.

1) String matching:-

Suppose there are 2 strings.

 $A = \{x_1, x_2, \dots, x_m\}$ $B = \{y_1, y_2, \dots, y_m\}$ Write algorithm which print +1, 0 or -1 if $A > B$, $A = B$, $A < B$ respectively.

A	a	b	c
---	---	---	---

B	a	b	d
---	---	---	---

logic

```

while (t1 → data == t2 → data)
{
    increment t1, t2
}
if (t1 → data > t2 → data)
{
    A is greater
}
else - B is greater.

```

If (length of string (A) > length of string (B)) & vice versa A is greater & vice versa.

Algorithm →

strcat (A, B)

```

{
    // A - is pointing to first string.
    // B - is pointing to 2nd string.
    // t1 be a pointer pointing to A.


```

```

while (A → link != φ And B → link != φ)
{

```

2) If $X = (x_1, x_2, \dots, x_m)$ & $Y = (y_1, y_2, \dots, y_n)$ are the strings where x_i & y_i are the letters of the alphabet then $X < Y$, if $x_i = y_i$ for $1 \leq i \leq j$ and $x_{j+1} < y_{j+1}$ or if $x_i = y_i$ for $1 \leq i \leq m$ and $m < n$. Write an algorithm which takes two strings X & Y and returns either -1, 0 or +1 if $X < Y$, $X = Y$ or $X > Y$ respectively.



Algorithm →

STRCMP(X, Y)

```

{
    while (X != NULL and Y != NULL)
    {
        if (DATA(X) < DATA(Y))
        {
            return (-1)
        }
    }
}

```

```

if (DATA(X) > DATA(Y))
{
    return (+1);
}

if (DATA(X) == DATA(Y))
{
    X = LINK(X);
    Y = LINK(Y);
}

if (X == NULL and Y == NULL)
{
    return (0);
}

if (X != NULL)
{
    return (+1);
}

if (Y != NULL)
{
    return (-1);
}

```

3) Consider two strings S and PAT.
Write a program to check whether 'PAT' is substring of S.

⇒ eg:- S = "abcdef"
PAT = "de"

∴ PAT ⊆ S

PAT = "de"

Algorithm :-

STRMAT (S, PAT)

```

{
    T = S      // T is a pointer pointing to S
    X = PAT    // X is a pointer pointing to PAT
}

```

While (T != NULL)

```

{
    While (PAT != NULL)
    {
        if (DATA(S) == DATA(PAT))
        {
            S → LINK(S);
            PAT → LINK(PAT);
        }
        else
        {
            break;
        }
    }
}

```

```

if (PAT == NULL)
{
    "Substring matched"
    return (0);
}

```

```

else
{
    T = LINK(T);
    S = T;
    PAT = X;
}

```

```

}
print "PAT is not substring".

```


Assigns →

- 1) Program to convert infix exp^r to postfix.
- 2) Prog. to convert postfix exp^r to infix.
- 3) Prog. to add element & delete element from Circular queue without flag.
- 4) Prog. to add element in & delete element from stack using singly linked list.
- 5) Prog. to add element from doubly linked list.
- 6) Prog. to add two polynomials using singly linked list.
- 7) Prog. to compare 2 strings using singly linked list.
- 8) Binary tree traversal.
- 9) Depth first search.
- 10) Breadth first search.
- 11) Prog. to add record & delete record from Sequential file.
- 12) Prog. to add record & delete record from direct access file.

* A single link list is used to store list & single variable polynomial.

Generalised lists:-

A generalized list 'A' denoted by $A = (x_1, x_2, \dots, x_n)$ where x_i are for $1 \leq i \leq n$ are either

atom or list. If x_i is the list known as sublist of list 'A'.
'A' is the name of the list and x_1 is the head of list A and $(x_2, \dots, x_n)$ is called tail.

* Use of generalised list to represent ordered list.

Generalised list →

Tag	Data	Link
-----	------	------

i) $A = (\phi)$: $A = \phi$

ii) $A = (a, b)$

$A \rightarrow [0 | a | \rightarrow 0 | b | \phi]$

iii) $A = (a, (b, c))$: $A \rightarrow [0 | a | \rightarrow 1 | \phi]$

$\downarrow$ pointer
 $[0 | b | \rightarrow 0 | c | \phi]$


iv) $A = ((b, c), a, (d, e))$

$A \rightarrow [1 | \phi] \rightarrow [0 | a | \rightarrow 1 | \phi]$


$\downarrow$
 $[0 | b | \rightarrow 0 | c | \phi]$

$\downarrow$
 $[0 | d | \rightarrow 0 | e | \phi]$


$$v) \quad A = ((cd), a), a$$



$$vi) \quad A = (a, A)$$




$$vii) \quad A = (a, B, A) \\ B = (a, b, c)$$




*2) Use of generalized list to store multivariable polynomial:-

COEF	EXP	LINK

$$i) \quad 3x^{10}$$



$$ii) \quad 3x^2y^3 = (3x^2)(y^3)$$





$$iii) \quad 3x^2y^3 + 13xy^3 = (3x^2 + 13x)y^3$$



$$iv) \quad 12x^2y^3 + 3x^2y + 3x^3y^3 + 3x^3y$$

$$= (12x^2 + 3x^3)y^3 + (3x^2 + 3x^3)y$$





S.N *

Dynamic Memory Management:-

In multiprocessing computer environment several programs reside in memory at same time. Different programs have different mem. requirement. Each program may require a contiguous storage blocks in variety or sizes. When execution of program is complete it ~~realize~~^{release} the mem. block allocated to it and this free block may now be allocated to another program. In dynamic environment mem. required by

A program is not known in advance. Again the block of mem. will be free in some order different from that in which they were allocated.

For eg:- Consider the small mem.
of size 1000 words and 5 programs

1 101 252 1000 words 392 599 1000 1000

1)

P_1 (101)	P_2 (151)	P_3 (610)	P_4 (311)	P_5 (201)	Free (401)
----------------	----------------	----------------	----------------	----------------	---------------

$\rightarrow$ 14 210 252 312 396


[Status of Memory]

P_1, P_2, P_3, P_4, P_5 make request of size
101, 151, 61, 81, 201 resp.

Assume that programs P_2, P_4 complete the execution & free the mem. used by them.

P_1 (101)	Free (101)	P_3 (61)	Free (81)	P_5 (201)	Free (401)
----------------	---------------	---------------	--------------	----------------	---------------



We know have 3 free blocks but not "contiguous". Hence further large block request (eg of block size 501) cannot be satisfied. Now P_5 completes its execution, then this block should be combined with its adjacent block which is free further large request can be satisfied.



Status of memory.

* DATA STRUCTURE TO REPRESENT FREE BLOCK

environment to
In dynamic allocation to represent
free block of required size
it is necessary to keep the track
of those blocks that are not in use -
All this free blocks can be maintained
in the linked list (chain form).
Each node in the free list has
two fields in its first word.
First field is size & 2nd field is
Link field.




Free list / chain structure of
free list

Allocation Strategies:-

- i) First - Fit :- When a block of size 'n' is requested then the free list is traversed sequentially to find the first free block whose size is greater than or equal to n. Once the block is found it is removed from the list and allocated (if size of block = n).
- otherwise the block is split into two blocks such that one block having the size equal to n & that block is allocated and remaining is still available in the free list.

eg:- n = 150




ii) Best - Fit :-

In this method when a request of size n is made the entire free list is traversed sequentially first & smallest free block whose size is greater than or equal to n is allocated.

eg:- n = 51




- 5) Worst - Fit:- In this method always the portion of largest free block is allocated.




* Boundary Tag Method:-

- i) First operation:- when request of block size 'n' then search free block of size greater than equal to n & allocate it i.e. remove it from free list.
- ii) 2nd operation:- Returning free block back to free list as well as check whether its neighbour are also free. If so then they can be combine into a single block.


To implement 2nd operation the node structure can be modified as shown below:-




The 1st & last word of each block are reserved for allocation information. First word of each free block has 4 fields, llink, rlink, tag and size. and the last word of free block having 2 fields namely tag & uplink. This free block structure assumes doubly linked list. Both tag fields are set to zero for free blocks. Uplink is used to point to the start of block.




Suppose P₂ is free.






suppose P_4 is free.



Now, if P_5 is also free. (then P_4 & P_5 are merged).



Condition of merging $\rightarrow$


if tag field of previous block last word of previous block is zero the merge.

eg:- As tag field of (949) is zero merge P_4 & P_5

* TREES :-

Defn:- A tree is finite set of one or more nodes such that there is a specially designated node called the root node and the remaining nodes are partition into 'n' ≥ 0 disjoint sets $T_1, T_2, \dots, T_n$ where each of this set is a tree. $T_1, T_2, \dots, T_n$ are called the subtrees of a root.

eg:-



i) The no. of subtree of a node is called its degree.

Node	degree
A	2
B, D	0
E	3

ii) The nodes that have degree zero are called leaf nodes.

eg:- D, E, G, H, I, J.

iii) Degree of tree:- It is the max. degree of a node in the tree.

degree of tree = 3.

iv) The level of a node is defined by initially letting marking the root node at level one.

v) The ht. or depth of a tree is defined to be the maximum level of any node in the tree.



ht. of tree = 4.

vi) A forest is a set of $n > 0$ disjoint trees.

* Binary Tree:-

Ex: A binary tree is finite set of nodes which is either empty or consist of root and two disjoint binary tree called left subtree & right subtree.

eg:- a)



* Data Structure of binary tree:-

Structure BTree

declare ISEMTBT () $\rightarrow$ Boolean

CREATE () $\rightarrow$ btree

MAKEBT (btree, item, btree)
 $\rightarrow$ btree

LCHILD (btree) $\rightarrow$ btree

RCHILD (btree) $\rightarrow$ btree

DATA (btree) $\rightarrow$ item

all $l, d \in$ btree and $d \in$ item - let.

ISEMTBT (CREATE) $::=$ true

ISEMTBT (MAKEBT (l,d,r)) $::=$ false

LCHILD (MAKEBT (l,d,r)) $::=$ l

RCHILD (CREATE) $::=$ error

LCHILD (CREATE) $::=$ error.

DATA (MAKEBT (l,d,r)) $::=$ d

DATA (CREATE) $::=$ error

end

end

{ Create - Created a binary tree.

Make bt - Makes a new binary tree by adding l & right trees with d as

root node }.


Examples of binary tree:-

i)




Above fig. shows 2 binary trees. In 1st binary tree the right subtree is empty. Such binary tree is known as sparsely skewed binary tree to left.

ii)



For this binary node each node have zero subtree or 2 subtree. Such BT is known as complete binary tree.

iii)



In this binary tree have either 2 Subtree or zero subtree. All the nodes ^{having} ~~having~~ zero subtree are at same level. Such a binary tree is known as full binary tree.

a)

In full binary tree, (n) no. of node in particular, level = 2^{n-1} where $n = \text{level}$.

b)

The max. no of nodes in full b.t of depth $k = 2^{k+1} - 1$


*

Binary tree representation:-


i)

Array representation:-


A full binary tree of depth k is a binary tree having $2^{k+1} - 1$ nodes. In another word to represent binary tree of depth k the array size should be equal to $2^{k+1} - 1$




Size = $2^3 - 1 = 7$ nodes $\Rightarrow$ max array size




lchild = $2 \times i$ (i = index no. of array)
 rchild = $(2 \times i) + 1$
 parent = $\frac{i}{2}$



array size = $2^4 - 1 = 15$





Rough:




*b) Linked List to represent binary tree.

Node structure:



* Creation of Binary Tree:-

eg:- 10, 5, 8, 7, 15, 20, -1, 2



* Algorithm to Create & Implement tree:-

CREATEBT (A)

{ // R $\rightarrow$ Root
 // Temp $\rightarrow$ Node of tree
 // data $\rightarrow$ data
 } FIELDS —
 Data, LLink, RLink.

```

Create Root Node {
    R = NULL
    Read x (data 1)
    GETNODE (R)
    DATA (R) = x
    LINK (R) = R; RLINK (R) = NULL

    Print "How many values?"
    Read n
    for (1 to n)
    {
        Read x (new data)
        GETNODE (Tmp)
        DATA (Tmp) = x
        LLINK (Tmp) = RLINK (Tmp) = NULL

        while (1)
        {
            if (DATA (T) <= x)
            {
                if (LLINK (T) = NULL)
                {
                    LLINK (T) = Tmp;
                    break;
                }
                T = LLINK (T)
            }
            if (DATA (T) > x)
            {
                if (RLINK (T) = NULL)
                {
                    RLINK (T) = Tmp;
                }
            }
        }
    }
}

```

```

T = RLINK (T);
}
}

```

Q *


Binary Tree Traversal :- (To print binary tree).

There are 3 binary tree traversal algorithm available:-

- Inorder
- Post order traversal
- Pre order traversal


i) Inorder :- (LDR)

consider B.T.



Print → A + B * C
 Left | Right
 data


ii)



DATE: / /


PAGE NO: /

DATE: / /




* Postorder: (LRD) →

eg-1)



2)




Inorder: DCBEAFIHJG

* Preorder: (DLR) →

i)



ii)



Preorder: ABCDEFGHIJ

*

Inorder (T)

```
{ // T is a pointer to tree.
  // Node fields: DATA, RCHILD, LCHILD
  if (T not equal to NULL)
  { Inorder (LCHILD(T))
    Print DATA (T)
    Inorder (RCHILD(T))
  } }
```

*

Postorder (T)

```
{ if (T not equal to NULL)
  { }
```

```

Postorder (LCHILD(T))
Postorder (RCHILD(T))
Print: DATA(T)
}
}

```

* Preorder (T)

```

{
if (T != NULL)
{
print DATA(T)
preorder (LCHILD(T))
preorder (RCHILD(T))
}
}

```

1:

& traverse

Prog. to create ~~inorder~~ binary tree in inorder, preorder & postorder.

* Head Threaded Binary Tree:-


In a binary tree there are many null links at the leaf nodes.

In threaded binary tree this NULL links can be utilised by a pointer known as threads. These threads are pointing to nodes as follows:-

If (RCHILD (P) is equal to NULL)



we will replace it by pointer to node which would be printed after P when traversing the tree in inorder. Similarly when LCHILD (T) = NULL then it is replaced by a pointer to the node which immediately precedes the node P in inorder.

eg:-



for eg:-
(inorder)

(G C B F D E A H J)
only in NULL fields



Inorder - H E C F D G B A

Page No.:
DATE: / /


Page No.:
DATE: / /

* i) Head node is used for the efficient programming.

ii) NULL conditions are avoided.

* To ~~store~~ Distinguish between the Thread & pointer two extra bit fields known as Lbit & Rbit are added to the structure of node. If LCHILD(P) or RCHILD(P) is a normal pointer then LBIT(P) is set to 1. If LBIT(P) or RBIT(P) is thread then it is set to 0.

Eg:-



* Advantages:-

i) It simplifies inorder, preorder, postorder algorithms.

ii) In a binary tree if there are n nodes then there are $(n+1)$ NULL links. In threaded binary tree this ^{but} $(n+1)$ NULL links are also utilized.

* Binary Search Tree:-


Def:- A binary search tree (T) is a binary tree, either empty or each node in the tree contains an identifier and,

i) All identifiers in left subtree of tree are less than the identifier in root node of T.

ii) All identifiers in right subtree of tree are greater than the identifier in root node of T.

iii) Left & right subtrees of T are also binary search tree.

Eg:-



To search and identify 'x' in binary search tree x is compared with root. If $x < \text{identifier}$ then search continues in left subtree. If $x = \text{identifier}$ the search terminates.

In evaluating binary search tree it is useful to add special nodes

at every place there is NULL link known as external node, denoted by square boxes.

Each time a binary tree is examined for an identifier which is not in tree then search terminates at external node, i.e. we can say that search is unsuccessful; hence external nodes are also known as "failure node".

* External path length:-


It is the path length of binary tree. It is evaluated by sum over all the external nodes of the lengths of path from the root to these nodes.

eg. External path length of $a = 3$.
Internal path length of $-5 = 2$

* Weighted external path length:-

It is the summation of $\sum_{i=1}^{n+1} q_i k_i$, where k_i is distance from root node to external node with weight q_i .

$$\text{Wt. ext path length} = 2 \times 3 + 3 \times 3 + 5 \times 3 + 8 \times 3 + \dots + 100 \times 3$$





$$\begin{aligned} \text{Ex wt. external path length} &= 1 \times 3 + 2 \times 3 + 2 \times 3 \\ &\quad + 3 \times 3 + 4 \times 1 \\ &= 28 \end{aligned}$$

* Binary search tree with minimal weighted external path length:-

1. Huffman algorithm to construct minimal weighted ext. path length (binary tree). optimal

$$\begin{aligned} \text{eg:- } q_1 &= 2, q_2 = 3, q_3 = 5 \\ q_4 &= 7, q_5 = 9, q_6 = 13 \end{aligned}$$





Optimal Binary Tree

- 8) Construct minimal weighted external path length in above ex.

$$\begin{aligned} \text{Minimal wt path length} &= 7 \times 2 + 9 \times 2 + 2 \times 4 + 3 \times 4 \\ &\quad + 5 \times 3 + 13 \times 2 \\ &= 93 \end{aligned}$$

* Height Balance Binary Search tree


Defn. - An empty tree is height balanced.

If tree is non empty binary tree with T_L & T_R as its left and right subtrees, then T is height balance, if


- T_L and T_R are height balanced and
- $|h_L - h_R| \leq 1$

where h_L & h_R are the heights of T_L & T_R respectively.

* Balance factor of a tree T denoted by of a node ' T ' in a binary tree ' T ' is defined to be $h_L - h_R$, where h_L & h_R are height of left and right subtrees of T . Balance factor always betⁿ -1, 0 & +1




- b) balanced tree




$h_R = 0$
 $h_L = 1$
 $\therefore H = 1$ ($\therefore$ balanced)

c)




Ht. of tree
 $H = 2$
 $\therefore$ Tree is unbalanced

d)



Ht. of tree betⁿ
 $2-1 = 1$
 $\therefore$ balanced.

e)



* unbalanced

Page No. _____

DATE : / /

Page No. _____

DATE : / /

* When height of tree is unbalanced
Re-balancing can be carried out by
4 types of rotation:-

- i) L-L
- ii) L-R
- R-L
- & R-R

This rotation are char' by the
nearest ancestor (A) of inserted
node 'y' whose balance factor becomes
 ± 2 .

- i) L-L:- New node 'y' is inserted
in left subtree of left subtree of A.
- ii) L-R:- New node 'y' is inserted
in right subtree of left subtree of A.
- iii) R-L:- New node 'y' is inserted
in left subtree of right subtree of A.
- iv) R-R:- New node 'y' is inserted
in right subtree of right subtree of A.

* SEQUENTIAL FILE HANDLING:-

* Basic Operatⁿ:-

- i) Create
- ii) Open
- iii) Close

Additionalⁿ → i) Read → Search
ii) Write → addition.
iii) Read & write → update.
iv) Deletion.
 ↳ a) Reorganisation.
 ↳ b) Flag method.

* Assign - 9 :- /* Sequential file processing */

```

struct STUD
{
    int Roll;
    char Name[30];
    char Class[6];
} S;
char FILENAME[30];

```

```

main()
{

```

```

    char choice;
    while (1)
    {

```

```

        clrscr();
    }
}

```



```

printf("\n Create");
printf("\n Open");
printf("\n Write");
printf("\n Search");
printf("\n Update");
printf("\n Delete");
printf("\n Exit");
choice = getch();
switch (choice)

```

```

{
    case 'C': Create();
                break;
    case 'O': Open();
                break;
}

```

Before
(main)

```

void Create (void)
{
    FILE *fp;
    printf("\n Enter the name to create");
    scanf("%s", FileName);
    fp = fopen(FileName, "w");
    if (fp == NULL)
    {
        printf("FILE CREATION ERROR");
        return;
    }
    fclose(fp);
}

```

```

void open (void)

```

```

{
    FILE *fp;
    printf("\n Enter the filename");
    scanf("%s", FileName);
    fp = fopen(FileName, "r");
    if (fp == NULL)
    {
        printf("CREATE FILE FIRST");
        return;
    }
    fclose(fp);
}

```

```

void Write (void)

```

```

{
    FILE *fp;
    fp = fopen(FileName, "a");
    if (fp == NULL)
    {
        printf("CREATE FILE FIRST");
        return;
    }
    printf("\n Enter the Record");
    scanf("%d %s %s", &s.Roll, s.Name, s.class);
    fseek(fp, 0, SEEK_END);
    fwrite(&s, sizeof(struct stud), 1, fp);
    fclose(fp);
}

```

```
void Search (void)
```

```
{
    FILE *fp; int n;
    fp = fopen (FILENAME, "r");
    printf ("Enter the Roll no. to be
           searched");
    scanf ("%d", &n);

    while (!feof (fp))
    {
        fread (&s, sizeof (struct STUD), 1, fp);
        if (s.Roll == n)
        {
            printf ("Record is = %s, %s", s.Name,
                   s.Class);
            fclose(fp);
            return;
        }
    }
    printf ("Not Found");
    fclose(fp);
}
```

```
* void update (void)
```

```
{
    FILE *fp; int n; long pos;
    fp = fopen (FILENAME, "r+");
    if (fp == NULL)
```

```
printf ("\n Roll no. of Record to be
        update");
```

```
scanf ("%d", &n);
while (!feof (fp))
{
    pos = ftell (fp);
    fread (&s, sizeof (struct STUD), 1, fp);
    if (s.Roll == n)
    {
        printf ("\n Reenter the record of %d", n);
        scanf ("%s %s", s.Name, s.Class);
        fseek (fp, pos, SEEK_SET);
        fwrite (&s, sizeof (struct STUD), 1, fp);
        fclose (fp);
        return;
    }
}
```

```
printf ("\n RECORD NOT FOUND");
fclose (fp);
```

```
void Delete (void) [if Roll no = 0
                    assumed deleted]
```


```
SEARCH the roll no
```

```
s.Roll = 0;
fseek (fp, pos, SEEK_SET);
fwrite (&s, sizeof (---), 1, fp);
fclose (fp);
return;
```

```
void Listing (void).
```

```
{
    FILE *fp;
    int n;
    for
    fp = fopen (Filename, "r");
    if (fp == NULL)
    {
    }
    while (!feof(fp))
    {
        fread (&s, sizeof(struct stud), 1, fp);
        if (s.Roll != 0)
        {
            printf ("In Roll No = %d, Name = %s\n", s.Roll, s.Name, s.class);
        }
    }
    fclose(fp);
    return;
}
```

* Hash Table :-



Hash functions :-

Divide & remainder method :-

Roll No	Data
0	
1	
2	
3	
4	
5	
6	
7	
8	
9	

For Roll No 1 :- size of array/struct

formula :- $Roll = (Roll - 1) \text{ mod } 10$

it returns 0 (i.e. first roll no)

i) Folding :-

a c c	c a a
1 3 3	1 1 1
	3 1 1

pos = 100
+ 30
7 5
133

pos = 300
+ 10
7 1
311

iii) Mid & square, -

Q) * A hash table is used to store 12 records. The size of hash table is 6. Assume total slots = 2. Hash function is divide & remainder. Key values are 10, 100, 8, 7, 5, 13, 0, 9, 65, 50. Show the status of hash table after inserting key values in order.

OR. HASH METHOD USING LINEAR PROBING

	1	2	
	N = 6		
	Slots = 2		
0	12	0	
1	7	21	Hashf = key mod N
2	8	50	funcn value
3	9	14	overflow ex - (10 % 6 = 4
4	10	100	10 will be in 4th slot)
5	5	65	As hashtable is Circular (21 mod 6 = 3)
			is in posn 2nd)

LINEAR PROBING is used to search given overflow element. [For this jump to original position & then search until the pointer reaches the original position].

Assg. - 10

* Program to Create Hash table *

```

struct { Assume marks are bet 0 to 9 }
{
    int marks;
    char Name[30];
} HT[10][2];

```

Void Insert(void)





```

{
    pos, i;
    int m; char n[30]
    printf("Enter the Marks & Name.");
    scanf("%d %s", &m, n);
    pos = m % 10;
    for (i = 0; i < 2; i++)
    {
        if (HT[pos][i].marks == -1)
        {
            HT[pos][i].marks = m;
            strcpy(HT[pos][i].name, n);
            return;
        }
    }
    pos = (pos + 1) % 10
    for (i = 0; i < 10; i++)
    {
        for (j = 0; j < 2; j++)
        {
            if (HT[pos][j].marks == -1)
            {
                break;
            }
        }
    }
}

```

$$pos = (pos + 1) \% 10$$

Rotations: (429)








Ex. Construct a ht. balance tree for, wed, Tue, Mon, Sat, Thu, Fri, sun.

i) Insert wed



ii) Insert Tue:-






Theory

Hash table - 456 (Page no.)

Hashing functⁿ - 458

Overflow - 462

Overflow handling technique - 462
(i.e. linear probing)Chaining - 467
H-Ttypes:- chaining with replacement
- without -

DATE: 23/03/2009

DATE: / /

* Continued in C-book.

* Index sequential ^{File} ~~Matrix~~ :-

a) The record can be access using index. Index is nothing but a structure that contain the ~~the~~ information

1) key value, ii) Location of Record.

b) Searching is faster as compared to seq., relative & direct access file.

Disadv → Deletⁿ is complicated.

* Primitive operatⁿ:-

1) All operatⁿ are same to as direct access file.

* Linear index file:-

If the index file is ordered by value (ascending/descending) then such file is known as linear index file.

* Tree indexes:-

Tree index is one in which there is hierarchy of index. The root of 1st level of the index points to second level of the index. Each level of the index pts to the lower level until the lowest node, (leaf node) are reached. The leaf node have pointers only to data file.

Tree indexes are classified into

2 Types :-

i) Heterogenous tree index


ii) Homogenous

} ②

i) Heterogenous tree index:-


a) Structure of Node:-


Each ~~tree~~ node except the leaf node contains ~~two~~ fields as shown below.



ex) let n=3 :-

suppose abh





* Homogeneous tree index:-


a) Structure of node →

Tree pointer 1	Key 1
Data pointer 1	Tree pointer 2
Key 2	Data pointer 2
Tree pointer n	Key n
Data pointer n	Tree pointer n+1
Key n+1	Data pt. n+1

Each node contains 2 types of data pointer & other is tree pointer. Generally no. of keys is equal to no. of data pointers.

To search any record searching begins from 1st record. Given key is compared with key value in node. Result will be either match is found or value lies betn 2 keys. If the match is found ^{then} corresponding data

pt. is used to access record, otherwise corresponding tree pointer is used to search the next node & process is repeated.



Data pointers = No. of keys.

Tree pointers = Data pointers + 1

* Searching time is ^{less} ~~for~~, as record ~~can~~ is found at each level.

* Re

* Relative File :-

Struct RECORD

```

{
    int Roll;
    char Name[30];
} s;
#define SIZE 70
char FileName[30];
void create (void)
{
    FILE *fp;
    fp = fopen (FileName, "w");
    if (fp == NULL)
    {
        printf (" ");
    }
    s.Roll = 0;
    for (i=0; i<SIZE; i++)
    {
        fwrite (&s, sizeof (struct RECORD), 1, fp);
    }
    fclose(fp);
}

```

Void Addition (Void)

```

{ int key, long pos;
FILE *fp = fopen (FileName, "r+");
if (fp == NULL)

```

check for
dupli
cates/overwrites

```

printf ("Enter Roll");
scanf ("%d", &key);
pos = (key-1) * sizeof (struct RECORD);
fseek (fp, pos, SEEK_SET);
fread (&s, sizeof (struct RECORD), 1, fp);
printf ("Enter the name");
scanf ("%s", s.Name);
s.Roll = key;
fwrite (&s, sizeof (struct RECORD), 1, fp);
fclose (fp);
}

```

void Search (void)

```

{
    int key, long pos;
    FILE *fp;
    fp = fopen (FileName, "r+");

    printf ("Enter the Roll No");
    scanf ("%d", &key);
    pos = (key-1) * sizeof (struct RECORD);
    fseek (fp, pos, SEEK_SET);
    fread (&s, sizeof (struct RECORD), 1, fp);
    if (s.Roll == 0)
    {
        printf ("Record is deleted");
        fclose (fp);
        return;
    }
}

```

```

printf ("Roll No = %d, Name = %s", s.Roll, s.Name);

```



```
fclose (fp);
```

```
}
```

```
* Index Seq. File :-
```

```
struct Index
{
    int Roll;
    long pos;
} I;
```

```
int Roll /* Key */
```

```
char Name [30];
```

```
{s;
```

```
char Indexfile [30]; Datafile [30];
```

```
void Create (void)
```

```
{ FILE *fpIndex, *fpData;
```

```
printf ("Enter Index file & Data filename")
```

```
scanf ("%s %s", Indexfile, Datafile);
```

```
fpIndex = fopen (Indexfile, "w");
```

```
fpData = fopen (Datafile, "w");
```

```
fclose (fpIndex);
```

```
fclose (fpData);
```

```
}
```

```
void Addition (void)
```

```
{
```

```
long pos;
```

```
FILE *fpIndex, *fpData;
```

```
fpIndex = fopen (Indexfile, "a");
```

```
fpData = fopen (Datafile, "a");
```

IS Name
for storing
only Name
in Data file

```
printf ("Enter Roll");
```

```
scanf ("%d", &s.Roll);
```

```
printf ("Enter Name");
```

```
scanf ("%s", s.Name);
```

```
fwrite (&s, sizeof (---), 1, fpData);
```

```
pos = ftell (fpData);
```

```
pos = pos - sizeof (struct RECORD);
```

```
I.Roll = s.Roll;
```

```
I.Pos = pos;
```

```
fwrite (&I, sizeof (struct Index), 1, fpIndex);
```

```
fclose (fpData);
```

```
fclose (fpIndex);
```

```
}
```

```
void Search (void)
```

```
{
```

```
FILE *fpIndex, *fpData;
```

```
long pos;
```

```
fpIndex = fopen (Indexfile, "r");
```

```
fpData = fopen (Datafile, "r");
```

```
printf ("Enter Roll No");
```

```
scanf ("%d", &key);
```

```
while (!feof (fpIndex))
```

```
{
```

```
fread (&I, sizeof (struct Index), 1, fpIndex);
```

```
if (I.Roll == key)
```

```
{
```

```
fseek (fpData, I.Pos, SEEK_SET);
```

```
fread (&s, sizeof (struct RECORD), 1, fpData);
```

```
}
```

```

printf ("Roll No = %d, N = %s", S.Roll, S.Name);
fclose(fp); return;
} // End of while //
printf ("Not Found");
fclose(fp); (fp Index);
}


```

* B-Tree :-

* B-Tree is a tree of order m is homogenous tree that is either empty or its height greater than equal to one & satisfying the following properties,


- The root node has atleast 2 children.
- All other nodes (other than root nodes) and leaf node (failure node) have atleast $n/2$ children.
- All the leaf node are at the same level.

ex:-




3-way search tree (i.e. $m=3$)


Fig. shows B-tree of order 3. Insert following key values in that tree. Key values - 38, 55, 37, 5, 18, 12




i) 38






ii) 55 :-







iii) 37 :-



iv) 5v) 18vi) 12

* 3011. fig. shows a btree of order 3.
Delete the foll. key values, 58, 65,
55 & 40

i) 58 :-ii) 65 :-iii) 55 :-iv) 40

* Overflow File :-


In direct access file when a new identifier is inserted into a full bucket then overflow occur. A simple solⁿ to handle this solⁿ is to place a new identifier into another file known as overflow file. overflow file can be organised as sequential/direct access file.

values of primary keys can be grouped into the ranges, so that searching time can be minimised.

eg:-

#Record	Roll No	Name	City
A	10	xyz	Dhule
B	12	per	Jalgaon
C	50	abc	London
D	80	a1	Dhule
E	82	a2	Dhule Dhule

* RetHashing :- It is the different method of handling the overflow. It requires 2 hashing functions. Main hashing funcⁿ is applied to identifier first, if the slot is already occupied then overflow occur. In this situatⁿ the 2nd hashing funcⁿ is applied.




ii) If key is secondary :-

Let (City) is the index in above ex.

* MultiList File organisation:-

To provide the facility of searching on each field of record it is necessary to maintain several index. One index is for each field. Again several record with same key values are possible. To reduce the searching time, & size of index file foll. criteria is used :-

i) If key is a primary key then the




A file in which records that share the value of fields linked together is called the Multilist file.

- * Construct the Multilist file of the given record below:- Assume employee no. range 10-20, 21-50, 51-100.

Record No.	Employee no.	Occupation	Salary	Experience
A	10	Programmer	8,000	4
B	15	Programmer	12,000	8
C	50	Analyst	10,000	10
D	80	Analyst	12,000	12
E	90	Programmer	12,000	12

Table (a)



Also do it for salary, & exp.


* Inverted File :-

It is similar to multilist file.

The diff. is that in the record with same key value are linked together with link information kept in the individual records. But in inverted file the link information is kept in index itself so that the index entries are variable in length.

or :- Consider Table (a).

20	50	100
2	1	2
A	C	D
B	-	E



Programmer	Analyst
A, B, E	C, D

ORIGINALITY REPORT

%7

SIMILARITY INDEX

%6

INTERNET SOURCES

%3

PUBLICATIONS

%

STUDENT PAPERS

PRIMARY SOURCES

1

www.southfayette.org

Internet Source

%4

2

www.roseburg.k12.or.us

Internet Source

%2

3

E. H. EASON. "The type specimens and identity of the species described in the genus *Lithobius* by F. Meinert, and now preserved in the Zoological Museum, Copenhagen University (Chilopoda: Lithobiomorpha)", *Zoological Journal of the Linnean Society*, 8/1974

Publication

%1

EXCLUDE QUOTES

ON

EXCLUDE MATCHES

< 4 WORDS
